

MANDARIN STONE

Adhesive & Grout Selector

PROPERTIES	PREPARATION	FIXING			FINISHING		
	PRO 30 FIBRE LEVELLING FLOOR SCREED (20kg)	STANDARD SET FLEX S1 (20kg)	RAPID SET FLEX S1 (20kg)	LARGE FORMAT FLEX (20kg)	FLEXIBLE GROUT (10kg)	4 IN 1 WALL & FLOOR GROUT (5kg)	4 IN 1 SILICONE (310ML)
COLOUR	Grey	White	Grey/ White	Grey	Various		
BED THICKNESS (MM)	0-30	3-6	2-10	5-25	N/A	N/A	N/A
SETTING TIME (HRS)	≤1.5	24	3	3	24	5	N/A
COVERAGE (M ²)**	≤5	3-5	3-5	0.5-3.5	7-15	7-15	N/A
JOINT WIDTH (MM)	N/A	N/A	N/A	N/A	3-12	1-8	4-25
FLOOR	√	√	√	√	√	√	√
WALL	x	√	√	x	√	√	√
INTERIOR	√	√	√	√	√	√	√
EXTERIOR	x	√	√	√	√	√	√
SUBSTRATES: FLOORS							
SAND/CEMENT SCREED	√	√	√	√	√	√	√
ANHYDRITE/ GYPSUM SCREED	√†	√†	√†	√†	√	√	√
U/F HEATED SCREED	√	√	√	√	√	√	√
UNDERTILE HEATING	√	√	√	√	√	√	√
GLAZED TILES	√#	√#	√#	√#	√	√	√
UNGLAZED TILES	√	√	√	√	√	√	√
VINYL TILES	√†	√†	√†	√†	√	√	√
PLYWOOD OVERLAY	√†	√†	√†	√†	√	√	√
CONSTRUCTION BOARD	√†	√†	√†	√†	√	√	√
SUBSTRATES: WALLS							
SAND/CEMENT RENDER	x	√	√	x	√	√	√
PLASTER BOARD	x	√†	√†	x	√	√	√
CONSTRUCTION BOARD	x	√	√	x	√	√	√
PLYWOOD	x	√†	√†	x	√	√	√
PLASTER SKIM ***	x	√†	√†	x	√	√	√
LEGEND							
†Use with Priming Agent							
#Use with slurry bonding coat (2 parts adhesive to 1 part priming agent)							

**NB. All coverage rates are approximate

***NB. Subject to weight of tile covering