



- UNPOLISHED NATURAL STONES AND AGGLOMERATES
- CONCRETE



### WHAT IT'S FOR

- Protects exterior pavings from water and humidity.
- Makes walls and claddings water-repellent.
- Ideal for brick veneers and concrete.
- Protects grout joints.
- Protects from wear caused by atmospheric agents.

### ADVANTAGES

- Gives a long-lasting, renewable protection that allows the material to breathe.
- Does not alter the appearance of the surface.
- Does not yellow despite environmental conditions or ageing.
- High penetration capacity.
- High coverage.
- Prevents formation of moss and mold.
- Certified as suitable for use on food contact surfaces.
- Prevents efflorescence.

#### COVERAGE

##### With one litre:

Natural stone	10/20 m <sup>2</sup>
Concrete	5 m <sup>2</sup>

"Coverage rates are approximate and refer to a single coat of the product"

### HOW IT'S USED

**No dilution:** ready to use

#### Application:

Apply an even, generous coat onto a perfectly clean and dry surface with brush or roller. On vertical surfaces, the airless spray method is recommended. Apply until no more product can be absorbed. Depending on the absorbency of the substrate, a second coat may be required, after 24 hours. On low-absorbency natural stone (such as slate) apply one coat. For concrete or more porous natural stone two coats are needed. On exterior surfaces where oil-repellency is also required, apply a finishing coat of FILAFOB after 24 hours.

#### Maintenance:

diluted solution of FILACLEANER

#### Caution:

When protecting low porosity natural stone, spot test the product in advance on a small trial surface to check for colour changes. Non applicare il prodotto nel caso sia prevista pioggia entro le 8 ore.

### Packaging

1 litre cans in box of 12.  
5 litre cans in box of 4.

#### PRECAUTIONS

- Keep out of the reach of children.
- Dispose of the container properly after use.
- Non protegge il marmo e le pietre calcaree dalle aggressioni acide.

Per essere trattato, un pavimento esterno deve essere posato a regola d' arte e cioè rispondere a tutti i requisiti richiesti del caso, come ad esempio: il rispetto delle pendenze, la corretta realizzazione di giunti di dilatazione, il perfetto isolamento del terreno, la comprovata ingelività del materiale.

#### TEMPERATURE

Storage temperature: between 0° C and 30° C.  
Must be applied to material at temperatures between 5° and 30° C.

#### COMPOSITION

Blend of siloxane compounds dispersed in de-aromatized hydrocarbon solvent.

#### LABELLING

WARNING: Danger

#### Hazard indication:

Flammable liquid and vapour. May be fatal if swallowed and enters airways. Repeated exposure may cause skin dryness or cracking.

#### Caution recommendations:

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat / sparks / open flames / hot surfaces. No smoking. Wear protective gloves / protective clothing / eye protection / face protection. IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician. Dispose of contents / container in accordance with official regulations.

Contains: NAPHTA (PETROL.) HYDROTREATED HEAVY



#### TECHNICAL INFORMATION

Appearance: liquid

Colour: colourless

Odour: slight odour of hydrocarbon solvent

Density: 0,777 kg/litre

Flash point: 40° C

The information above reflects our latest technical know-how and is the outcome of ongoing laboratory research and testing. However, some factors are beyond our control. It is essential to integrate our suggestions with your own on-site preliminary tests and check. Fila accepts no liability for improper use of its products.