## MANDARIN STONE

## **PRODUCT SPECIFICATION**

## FUSION RANGE PORCELAIN

Technical features - compliant with standards EN 14411 (ISO 13006) group B1a

Technical Features	Reference	Required Standards	Average Value
Dimensions of sides	ISO 10545-2	<u>+</u> 0.60%*	Conforms
Thickness		<u>+</u> 5.00%	Conforms
Straightness		<u>+</u> 0.50%	Conforms
Squareness		<u>+</u> 0.60%	Conforms
Flatness		<u>+</u> 0.50%	Conforms
Water Absorption	ISO 10545-3	<u>≤</u> 0.5%	Conforms
Modulus of Rupture	ISO 10545-4	R ≥ 35 N/mm <sup>2</sup>	Conforms
Linear Heat Expansion Coefficient	ISO 10545-8	Declared Value	≈ 7xIO <sup>-6</sup> C <sup>-I</sup>
Thermal Shock Resistance	ISO 10545-9	According to ISO 10545-1	Resistant
Frost Resistance	ISO 10545-12	Required	Resistant
Slip resistance	BS EN 7976-2	Slip Resistant (≥0.36)	NPD
Non-slip classification	DIN 51130	— Declared Value	Rio
	DIN 51097		А
Resistance to Chemical Attack	ISO 10545-13	Declared Value	Resistant
Resistance to stains	ISO 10545-14	Declared Value	≥ Class 3